IN THE CLAIMS:

Please amend Claims 1, 10 and 19 as follows. Note that all the claims currently pending in this application, including those not presently amended, have been reproduced below for the Examiner's convenience.

- 1. (Currently Amended) A semiconductor manufacturing apparatus comprising:
 - a light source; and
 - a lighting device, said lighting device comprising:
 - (i) an electrical power source unit for supplying electricity to said light source,

and

(ii) a starter unit for lighting said light source,

wherein a first unit coupled to the lighting device moves the lighting device in a first direction and a second unit coupled to the lighting device moves the lighting device in a second direction, and

wherein said starter unit has includes a metal piece for connecting said lighting device to said light source, and a third unit for moving the metal piece and the connected light source relative to the connected lighting device in a third direction.

2. (Original) A semiconductor manufacturing apparatus according to Claim 1, wherein said light source is a discharge lamp.

- 3. (Original) A semiconductor manufacturing apparatus according to Claim 1, wherein said metal piece is disposed at a side wherein high voltage is applied for lighting said light source.
- 4. (Original) A semiconductor manufacturing apparatus according to Claim 1, further comprising a mechanism for integrally driving said light source and said lighting device.
- 5. (Original) A semiconductor manufacturing apparatus according to Claim 1, further comprising means for changing the positional relation between said light source and an optical element disposed near said light source.
- 6. (Original) A semiconductor manufacturing apparatus according to Claim 1, wherein said light source and said lighting device are disposed within a single housing.
- 7. (Original) A semiconductor manufacturing apparatus according to Claim 6, wherein said housing has outer walls provided with electromagnetic shielding and has a configuration of copper wire mesh sandwiched between thermal insulating material, said copper wire mesh being grounded.
- 8. (Original) A semiconductor manufacturing apparatus according to Claim 6, wherein the temperature of said light source and said lighting device is adjusted using air of the

ambient atmosphere from outside said housing, taken into said housing from a single air intake and being subjected to temperature adjustment with a single temperature adjusting means.

- 9. (Original) A semiconductor manufacturing apparatus according to Claim 8, wherein said light source and said lighting device are subjected to temperature adjustment in the order of said lighting device first and then said light source, using the taken in air.
 - 10. (Currently Amended) A semiconductor manufacturing apparatus comprising: a light source;
 - a lighting device for lighting said light source; and
- a connector for connecting said light source and said lighting device with a metal piece, and;

a first unit coupled to the lighting device for moving the lighting device in a first direction;

a second unit coupled to the lighting device for moving the lighting device in a second direction; and

a <u>third</u> unit <u>in the lighting device</u> for moving the metal piece and the connected light source relative to the connected lighting device <u>in a third direction</u>.

11. (Original) A semiconductor manufacturing apparatus according to Claim 10, wherein said light source is a discharge lamp.

- 12. (Original) A semiconductor manufacturing apparatus according to Claim 10, wherein said light source and said lighting device are disposed within a single housing.
- 13. (Original) A semiconductor manufacturing apparatus according to Claim 12, wherein said housing has outer walls provided with electromagnetic shielding and has a configuration of copper wire mesh sandwiched between thermal insulating material, said copper wire mesh being grounded.
- 14. (Original) A semiconductor manufacturing apparatus according to Claim 10, wherein said metal piece is disposed at a side wherein high voltage is applied for lighting said light source.
- 15. (Original) A semiconductor manufacturing apparatus according to Claim 10, further comprising a mechanism for integrally driving said light source and said lighting device.
- 16. (Original) A semiconductor manufacturing apparatus according to Claim 10, further comprising means for changing the positional relation between said light source and an optical element disposed near said light source.
- 17. (Original) A semiconductor manufacturing apparatus according to Claim 12, wherein the temperature of said' light source and said lighting device is adjusted using air of the

ambient atmosphere outside said housing, taken into said housing from a single air intake and being subjected to temperature adjustment with a single temperature adjusting means.

- 18. (Original) A semiconductor manufacturing apparatus according to Claim 17, wherein said light source and said lighting device are subjected to temperature adjustment in the order of said lighting device first and then said light source, using the taken in air.
- 19. (Currently Amended) A semiconductor manufacturing apparatus in which a computer having a display, a network interface, and networking software provides data communication of maintenance information through a computer network, said semiconductor manufacturing apparatus comprising a lamp box including:
 - a light source;
 - a lighting device for lighting said light source; and
- a connector for connecting said light source and said lighting device with a metal piece, and;
- a first unit coupled to the lighting device for moving the lighting device in a first direction;
- a second unit coupled to the lighting device for moving the lighting device in a second direction; and
- a <u>third</u> unit <u>in the lighting device</u> for moving the metal piece and the connected light source relative to the connected lighting device <u>in a third direction</u>.

- 20. (Original) A semiconductor manufacturing apparatus according to Claim 19, wherein said networking software provides, on said display, a user interface for accessing a maintenance database which is provided by a vendor or user of said semiconductor manufacturing apparatus and which is connected to an external network outside of a plant wherein said semiconductor manufacturing apparatus is installed, thereby enabling information to be obtained from said database via said external network.
 - 21. (Withdrawn) A semiconductor device manufacturing method comprising the following steps:

a step of installing, in a semiconductor manufacturing plant, a set of manufacturing apparatuses for performing various processes, including the semiconductor manufacturing apparatus according to Claim 10; and

a step of manufacturing semiconductor devices by a plurality of processes using the set of manufacturing apparatuses.

22. (Withdrawn) A semiconductor device manufacturing method according to Claim 21, further comprising the following steps:

a step of connecting the set of manufacturing apparatuses by a Local Area Network; and

a step of performing data communication of information relating to at least one apparatus of the set of manufacturing apparatuses, between the Local Area Network and the

external network outside of the semiconductor manufacturing plant.

- 23. (Withdrawn) A semiconductor device manufacturing method according to Claim 22, further comprising accessing a database, which is provided by a vendor or user of the semiconductor manufacturing apparatus, via the external network and obtaining maintenance information for the manufacturing apparatus by data communication, or performing data communication with a semiconductor manufacturing plant other than the semiconductor manufacturing plant, via the external network, so as to manage production.
- 24. (Withdrawn) A semiconductor manufacturing plant, comprising:
 a set of manufacturing apparatuses for performing various processes, the set
 including the semiconductor manufacturing apparatus according to Claim 10;
- a Local Area Network connecting said set of manufacturing apparatuses; and
 a gateway enabling access to an external network outside of said plant from said
 Local Area Networks,

wherein data communication of information relating to at least one apparatus of said set of manufacturing apparatuses is performed.

25. (Withdrawn) A maintenance method for the semiconductor manufacturing apparatus according to Claim 10 installed in a semiconductor manufacturing plant, said method comprising the following steps:

a step of a vendor or user of the semiconductor manufacturing apparatus

providing a maintenance database connected to an external network outside of the semiconductor

manufacturing plant;

a step of permitting access to the maintenance database from within semiconductor manufacturing plant via the external network; and

a step of transmitting maintenance information accumulated in the maintenance database to the semiconductor manufacturing plant side via the external network.